

# KOOLSEAL™

REFLECTIVE ROOF COATINGS

## PRODUCT PORTFOLIO





# THE KOOL SEAL EVOLUTION



**KOOL SEAL**  
REFLECTIVE ROOF COATINGS

1906

1920

1954

1984

2004

2005

2006

2014




Acorn Chemical & Refining founded in Cleveland, Ohio ( Later renamed KST Coatings)



Kool Seal brand introduced a line of roof coatings to address the needs of the residential marketplace.



KST introduced first aluminum reflective roof coating



KST introduced first elastomeric reflective roof coating



Kool Seal Dura Lite introduced as an innovative light-weight roof coating



KST Coatings acquired by Sherwin Williams



Built on a solid legacy of excellence, KST Coatings celebrated its 100th year in the roof coating market



Kool Seal goes through brand overhaul and introduces new rebranding



# NEW LABEL ARCHITECTURE

Delivering Premium Reflective Roof Coatings with a New Look



OLD



NEW





# NEW COLOR CODING CLASSIFICATION SYSTEM

Simplify the process of selecting the right product for your project with our new label color coding classification system



BLUE

KOOL SEAL® ELASTOMERIC ROOF COATINGS REFLECT HEAT AND HARMFUL UV RAYS, WHILE PROTECTING AGAINST THE ELEMENTS, EXTENDING THE LIFE OF THE ROOF



GRAY

KOOL SEAL® ASPHALTIC ROOF COATINGS ARE AVAILABLE IN BOTH FIBERED AND NON-FIBERED TO PROVIDE EXCELLENT WATERPROOFING CAPABILITIES



RED

STOP LEAKS AND ROOF DETERIORATION WITH KOOL SEAL® STORM PATCH® PATCH & REPAIR PRODUCTS



GREEN

KOOL SEAL® ASPHALT EMULSION DRIVEWAY SEALERS PROVIDE A WATERTIGHT, FLEXIBLE SEAL FOR ASPHALT SURFACES





# **ELASTOMERIC**

## *ROOF COATINGS*



PRODUCT NAME	Premium Elastomeric Finish Coat 12YR	Premium Elastomeric Finish Coat 10 YR	Elastomeric Finish Coat 7 YR	Elastomeric Finish Coat 5 YR	Elastomeric Base Coat
WARRANTY	12 Years	10 Years	7 Years	5 Years	Satisfaction Guarantee
TECHNOLOGY	100% Acrylic	100% Acrylic	100% Acrylic	100% Acrylic	100% Acrylic
FEATURES & BENEFITS	Premium performance that renews most roofing types Reflects heat and harmful UV rays Protects against the elements, extending the life of the roof Meets ASTM D 6083 and Title 24	Renews most roofing substrates Expands and contracts with roof Long lasting protection and reflectivity	Renews most roofing substrates Reflects heat and protects against the elements	Economy Grade Reflects heat and harmful UV rays	Provides maximum adhesion to all surfaces Provides an excellent surface for application of Kool Seal Elastomeric Finish Coats
RECOMMENDED SUBSTRATES	Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, EPDM, Hypalon, existing asphaltic and elastomeric roof coatings. Not for use on roof shingles	Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, EPDM, Hypalon, existing asphaltic and elastomeric roof coatings. Not for use on roof shingle	Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, EPDM, Hypalon, existing asphaltic and elastomeric roof coatings. Not for use on roof shingles	Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, EPDM, Hypalon, existing asphaltic and elastomeric roof coatings. Not for use on roof shingles	Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, EPDM, Hypalon, existing asphaltic and elastomeric roof coatings. Not for use on roof shingles
PART NUMBER / SMIS	KS0063900 / 1-Gallon, 5-Gallon	KS0063600 / 1-Gallon, 5-Gallon, 55-Gallon	KS0063300 White / Gallon, 5-Gallon, 55-Gallon KS0063320 Gray / 5-Gallon KS0063325 Black / 5-Gallon	KS0063000 / 5-Gallon	KS0034600 / 1-Gallon, 5-Gallon
COLOR	White	White	White, Gray, Black	White	Gray
COVERAGE RATE PER GALLON	Apply at 50-100 sq ft per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended	Apply at 50-100 sq ft per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended	Apply at 50-100 sq ft per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended	Apply at 50-100 sq ft per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended	Apply at 50-100 sq ft per gallon per coat. Rough/porous surfaces will require additional coating.
DRYING TIME	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours
APPLICATION	Medium Nap Roller, Broom, Spray	Medium Nap Roller, Broom, Spray	Medium Nap Roller, Broom, Spray	Medium Nap Roller, Broom, Spray	Medium Nap Roller, Broom, Spray
CLEAN UP	Warm, soapy water	Warm, soapy water	Warm, soapy water	Warm, soapy water	Warm, soapy water

\*\*Repair all cracks, breaks, open seams and other imperfections with Kool Seal® Storm Patch Acrylic Patching Cement and Kool Seal Storm Patch Patching Fabric.  
Apply Kool Seal Storm Patch Acrylic Rust Primer to existing rusted areas





# **ASPHALTIC**

## **ROOF COATINGS**





05  
YEAR  
WARRANTY



03  
YEAR  
WARRANTY



05  
YEAR  
WARRANTY



SG  
SATISFACTION  
GUARANTEE



SG  
SATISFACTION  
GUARANTEE

PRODUCT NAME	Premium Fibered Aluminum Roof Coating	Fibered Aluminum Roof Coating	Premium Non-Fibered Aluminum Roof Coating	Fibered Roof Coating	Non-Fibered Roof Coating
WARRANTY	5 Years	3 Years	5 Years	Satisfaction Guarantee	Satisfaction Guarantee
TECHNOLOGY	Asphalt	Asphalt	Asphalt	Asphalt	Asphalt
FEATURES & BENEFITS	Premium Grade reinforced with fiber for durability Reflects heat and harmful UV rays Protects against the elements, extending the life of the roof	Economy Grade Reinforced with fiber for durability Reflects heat and harmful UV rays Protects against the elements, extending the life of the roof	Premium Grade Reflects heat and harmful UV rays Protects against the elements, extending the life of the roof	Restores and rejuvenates dried out asphalt surfaces such as smooth surface built-up and modified bitumen roofs.	Restores and rejuvenates dried out asphalt surfaces such as smooth surface built-up and modified bitumen roofs.
RECOMMENDED SUBSTRATES	Metal, aged aluminum coatings, rolled roofing, asphalt and modified bitumen	Metal, aged aluminum coatings, rolled roofing, asphalt and modified bitumen	Metal, aged aluminum coatings, rolled roofing, asphalt and modified bitumen	Asphalt surfaces such as smooth surface built-up and modified bitumen roofs. NOT FOR USE OVER COAL TAR SURFACES	Asphalt surfaces such as smooth surface built-up and modified bitumen roofs. NOT FOR USE OVER COAL TAR SURFACES
PART NUMBER / SMIS	KS0024600 / 1-Gallon, 5-Gallon	KS0024300 / 1-Gallon, 5-Gallon	KS0023600 / 1-Gallon, 5-Gallon	KS0024000 / 5-Gallon	KS0023000 / 5-Gallon
COLOR	Silver	Silver	Silver	Black	Black
COVERAGE RATE PER GALLON	Apply at 50-100 sq ft per gallon per coat. Two coats recommended	Apply at 50-100 sq ft per gallon per coat. Two coats recommended	Apply at 250-400 sq ft per gallon per coat. Two coats recommended	Apply at 50-100 sq. ft. per gallon per coat. Two coats recommended	Apply at 50-100 sq. ft. per gallon per coat. Two coats recommended
DRYING TIME	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 3-5 days	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 3-5 days	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 3-5 days	Exposure to rain or heavy dew : 12 hours Between coats and before foot traffic : 24 - 72 hours	Exposure to rain or heavy dew : 12 hours Between coats and before foot traffic : 24 - 72 hours
APPLICATION	Airless spray, low nap roller or broom	Airless spray, low nap roller or broom	Airless spray, low nap roller or broom	Roof brushes, squeegee or heavy duty spray equipment	Roof brushes, squeegee or heavy duty spray equipment
CLEAN UP	Mineral Spirits	Mineral Spirits	Mineral Spirits	Mineral Spirits	Mineral Spirits





**SEAL IT**

**KOOLSEAL**  
REFLECTIVE ROOF COATINGS



**PATCH IT**

# STORM PATCH


Have a leak in your roof, **PATCH** and **REPAIR** it.



**SPRAY IT**



**TAPE IT**

							
PRODUCT NAME	Asphalt Patch & Coat	Aluminum Roof Patch	Premium Wet/Dry Patching Cement Black Premium Wet/Dry Patching Cement Clear	Wet/Dry Patching Cement Black Wet/Dry Patching Cement Clear	Acrylic Patching Cerment White	Acrylic Rust Primer	Acrylic Concrete Primer
WARRANTY	Satisfaction Guarantee		Satisfaction Guarantee		Satisfaction Guarantee		Satisfaction Guarantee
TECHNOLOGY	Asphalt	Asphalt	Asphalt	Asphalt	Acrylic	Acrylic	Acrylic
FEATURES & BENEFITS	Water resistant roofing solution resists cracking and UV degradation  Applies easily with a brush for patching or can be rolled to coat roofs  Water-based for easy clean up	Suited for asphalt-based roofing substrates where an aluminum appearance is required  Remains soft and pliable in all types of weather  Seals, quickly to form a waterproof seal	Premium Performance that seals quickly, will not pull apart or lose it bond, remains soft and pliable.  Suited for asphalt-based roof substrates  Resists temperature change  Can be applied to wet or dry surfaces, even underwater	Suited for asphalt-based roofing substrates  Seals quickly, will not pull apart or lose it bond, remains soft and pliable.  Resists temperature change  Can be applied to wet or dry surfaces, even underwater	Blend of acrylic resin and reinforcing materials designed to stop leaks in damp or dry surface conditions  Seals out water and resists mildew and weathering when cured	Corrision resistant primer for metal roofs  Excellent adhesion to difficult surfaces	Highly alkali and efflorescence resistant primer that can be applied to concrete surfaces with a pH of 6 to 13
RECOMMENDED SUBSTRATES	All asphaltic surfaces, rolled roofing, metal, slate, asphalt/ fiberglass shingles, chimney & pipe flashings, metal & wood gutters, compostion roofs and driveway cracks	Metal, asphalt, smooth BUR, modified bitumen, rolled roofing, asphalt/fiberglass shingles and chimney flashings	Metal, asphalt, smooth BUR, modified bitumen, rolled roofing, apshalt/fiberglass shingles, chimney & pipe flashings. Do NOT use on shingle-ply membranes	Metal, asphalt, smooth BUR, modified bitumen, rolled roofing, apshalt/fiberglass shingles, chimney & pipe flashings. Do NOT use on shingle-ply membranes	Patching cracks, seams, holes & breaks around metal seams, parapet walls, chimney flashings, gutters, vents, stacks, skylights and air conditioners	All types of metal surfaces, including iron and steel where corrision is a problem	All concrete surfaces
PART NUMBER / SMIS	KS0081100 / 10 oz cartridge. 1 Gallon	KS0082100 / Quart, 1 Gallon	KS0083600 / 10 oz cartridge, 1 Gallon KS0083650 / 10 oz cartridge	KS0083300 / 10 oz cartridge, 1 Gallon KS0083350 / 10 oz cartridge	KS0085100 / 10.5 oz cartridge, 1-Gallon	KS0034800/ 1 Gallon, 5 Gallon	KS0034900 / 5-Gallon
COLOR	Black	Silver	KS0083600 / Black KS0083650 / Clear	KS0083300 / Black KS0083350 / Clear	White	250 sq. ft / gallon	White
COVERAGE RATE PER GALLON	For repairs, an overlayment thickness of 1/16" -1/8" is sufficient When used for resurfacing, spread at 2-4 gallons per 100 sq ft	15-25 sq ft / gallon	6-24 linear feet per cartridge depending on joint size  10-15 sq. ft / gallon (per coat)	6-24 linear feet per cartridge depending on joint size  10-15 sq. ft / gallon (per coat)	Will vary considerably depending on the type of surface coated and depth of cracks being repaired. In general, an overlayment thickness of 1/16 -1/8" is sufficient	Exposure to rain or heavy dew: 4-6 hours Between coats and before foot traffic: 24 hours	200 sq. ft / gallon
DRYING TIME	Exposure to rain or heavy dew : 12 hours Between coats and before foot traffic : 2-4 hours Before elastomeric or aluminum coatings: 30 days	Between coats : 24 hours Cures: 1-3 days	Between coats : 24 hours Cures: 1-3 days	Between coats : 24 hours Cures: 1-3 days"	Exposure to rain or heavy dew : 4-6 hours Between coats and before foot traffic : 24 hours minimum	Airless spray, low nap roller or broom at appropriate coverage rate	Exposure to rain or heavy dew : 4 hours Between coats and before foot traffic : 24 hours
APPLICATION	Roof brush or heavy nap roller	Trowel or putty knife	Trowel or putty knife	Trowel or putty knife	Roof Brush or stiff bristled paint brush	Warm, soapy water	Airless spray, low nap roller, broom
CLEAN UP	Warm, soapy water while wet. Mineral spirits when dry	Mineral Spirits	Mineral Spirits	Mineral Spirits	Warm, soapy water	Warm, soapy water	Warm, soapy water





PRODUCT NAME	Storm Patch® Rubberized Leak Sealer		Storm Patch® Galvanizing Primer	Storm Patch® Flexx Sealer Instant Leak Repair	Storm Patch® 4" Patching Fabric
WARRANTY	Satisfaction Guarantee		Satisfaction Guarantee	Satisfaction Guarantee	Satisfaction Guarantee
FEATURES & BENEFITS	Leak-free seal  Prevents moisture penetration and corrosion		Prevents corrosion on metal surfaces, gutters, downspouts, structural steel, galvanized surfaces, piping and more  Delivers superior protection in harsh elements  Suitable for “weld-through” applications	Stops leaks, seals instantly  Never cracks, peels or shrinks  Remains flexible	Seals out moisture and prevents leaks on roofs  Prevents cracks and splitting over seams  Easy to apply on all surfaces
RECOMMENDED SUBSTRATES	Metal, aluminum, masonry, plastic, asphalt/fiberglass shingles, cedar shake, acrylic roof coatings, cement and shake		Metal surfaces, gutters, down spouts, structural steel, galvanized surfaces, piping and more	Metal, asphalt, tar, fiberglass, plastic, rubber rv roofs and more	Seams, cracks joints, flashings, roof vents or where two unlike surfaces come together
PART NUMBER / SMIS	KS0065100-18 / 12 oz aerosol KS0065125-18 / 12 oz aerosol KS0065150-18 / 12 oz aerosol		KS0065200-18 / 12 oz aerosol	KS0018103-99 / 2" x 3' roll KS0018110-99 / 2" x 10' roll	KS0018304-99 / 4" x 50' roll
COLOR	KS0065100-18 White KS0065125-18 / Black KS0065150-18 / Clear		Gray	Gray	White
COVERAGE RATE PER GALLON	Up to 15 sq. ft		Up to 20 sq feet	KS0018103-99 / 3 feet KS0018110-99 / 10 feet	50 linear feet
DRYING TIME	To Touch: 10 minutes Can be coated with Kool Seal Elastomeric Coatings in 24 hours		To Touch: 15 minutes To Handle: 1-2 hours Full Cure: 7 days Additional coats within 2-16 hours or after 36 hours	N/A	N/A
CLEAN UP	Mineral Spirits		Mineral Spirits	N/A	N/A





# ***DRIVEWAY***

## ***ASPHALT EMULSION SEALERS***





07  
YEAR  
WARRANTY



05  
YEAR  
WARRANTY



03  
YEAR  
WARRANTY



SG  
SATISFACTION  
GUARANTEE



SG  
SATISFACTION  
GUARANTEE

PRODUCT NAME	Premium Emulsion Driveway Sealer & Filler -7 Year	Emulsion Driveway Sealer & Filler -5 Year	Emulsion Driveway Sealer-3 Year	Pourable Driveway Crack Filler	Trowel Grade Driveway Crack Filler
TECHNOLOGY	Asphalt Emulsion		Asphalt Emulsion		Asphalt
FEATURES & BENEFITS	Provides a watertight , flexible seal for asphalt surfaces Rejuvenates dried out asphalt surfaces Protects against the elements, extending the life of the surface Fills surface cracks Polymer modified for exceptional performance	Provides a watertight, flexible seal for asphalt surfaces Rejuvenates dried out asphalt surfaces Protects against the elements, extending the life of the surface Fills surface cracks	Provides a watertight, flexible seal for asphalt surfaces Rejuvenates dried out asphalt surfaces Protects against the elements, extending the life of the surface	Provides a watertight, flexible seal for asphalt and concrete surfaces Fills cracks up to 1/2" wide Protects against the elements, extending the life of the surface	Provides a watertight, flexible seal for asphalt and concrete surfaces Fills cracks up to 1" wide Protects against the elements, extending the life of the surface
RECOMMENDED SUBSTRATES	Asphalt Driveway Surfaces Do NOT apply to concrete		Asphalt Driveway Surfaces Do NOT apply to concrete		Fills cracks in asphalt & concrete joints Driveways & parking areas up to 1/2" width
PART NUMBER / SMIS	KS0073900	KS0073600	KS0073300	KS0075100	KS0075200
SIZE	5-Gallon, 55-Gallon Drum		5-Gallon, 55-Gallon Drum		1-Gallon
COLOR	Black	Black	Black	Black	Black
WARRANTY	7 Years	5 Years	3 Years	Satisfaction Guarantee	Satisfaction Guarantee



ELASTOMERIC ROOF COATINGS				
SKU DESCRIPTION	SKU NUMBER	SIZE	SIZE DESCRIPTION	QTY/CASE
KS Elastomeric Base Coat Gray	KS0034600	16 GAL	115 OZ / 0.9 GALLON	4
KS Elastomeric Base Coat Gray	KS0034600	20 PAIL	4.75 GALLON PAIL	1
KS Elastomeric Finish Coat White(5YR)	KS0063000	20 PAIL	4.75 GALLON PAIL	1
KS Elastomeric Finish Coat White (7YR)	KS0063300	16 GAL	115 OZ/ 0.9 GALLON	4
KS Elastomeric Finish Coat White (7YR)	KS0063300	20 PAIL	4.75 GALLON PAIL	1
KS Elastomeric Finish Coat (7YR)	KS0063300	27 DRUM	55 GALLON DRUM	1
KS Elastomeric Finish Coat Black (7YR)	KS0063325	20 PAIL	4.75 GALLON PAIL	1
KS Elastomeric Finish Coat Gray (7YR)	KS0063320	20 PAIL	4.75 GALLON PAIL	1
KS Premium Elastomeric Finish Coat White (10YR)	KS0063600	16 GAL	115 OZ/ 0.9 GALLON	4
KS Premium Elastomeric Finish Coat White (10YR)	KS0063600	20 PAIL	4.75 GALLON PAIL	1
KS Premium Elastomeric Finish Coat White (10YR)	KS0063600	27 DRUM	55 GALLON DRUM	1
KS Premium Elastomeric Finish Coat White (12YR)	KS0063900	16 GAL	115 OZ/ 0.9 GALLON	4
KS Premium Elastomeric Finish Coat White (12YR)	KS0063900	20 PAIL	4.75 GALLON PAIL	1

ALUMINUM ROOF COATINGS				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Fibered Aluminum Roof Coating (3YR)	KS0024300	16 GAL	115 OZ/ 0.9 GALLON	4
KS Fibered Aluminum Roof Coating (3YR)	KS0024300	20 PAIL	4.75 GALLON PAIL	1
KS Premium Fibered Aluminum Roof Coating (5YR)	KS0024600	16 GAL	115 OZ/ 0.9 GALLON	4
KS Premium Fibered Aluminum Roof Coating (5YR)	KS0024600	20 PAIL	4.75 GALLON PAIL	1
KS Premium Non-Fibered Aluminum Roof Coating (5YR)	KS0023600	16 GAL	115 OZ/ 0.9 GALLON	4
KS Premium Non-Fibered Aluminum Roof Coating (5YR)	KS0023600	20 PAIL	4.75 GALLON PAIL	1

ASPHALTIC ROOF COATINGS				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Fibered Roof Coating	KS0024000	20 PAIL	4.75 GALLON PAIL	1
KS Non-Fibered Roof and Foundation Coating	KS0023000	20 PAIL	4.75 GALLON PAIL	1

PATCH & REPAIR COATINGS				
SKU DESCRIPTION	SKU NUMBER	SIZE	SIZE DESCRIPTION	QTY/CASE
KS Asphalt Patch & Coat	KS0081100	16 GAL	115 OZ / 0.9 GALLON	4
KS Asphalt Patch & Coat	KS0081100	01 Cart	10 fl oz cartridge	12
KS Storm Patch Aluminum Roof Patch	KS0082100	14 Quart	28.75 oz Quart	4
KS Storm Patch Aluminum Roof Patch	KS0082100	16 GAL	115 OZ/ 0.9 GALLON	4
KS Storm Patch Wet/Dry Patching Cement Black	KS0083300	16 GAL	115 OZ/ 0.9 GALLON	4
KS Storm Patch Wet/Dry Patching Cement Black	KS0083300	01 Cart	10 fl oz cartridge	12
KS Storm Patch Wet/Dry Patch & Seal Clear	KS0083350	01 Cart	10 fl oz cartridge	12
KS Storm Patch Premium Wet/Dry Patching Cement Black	KS0083600	16 GAL	115 OZ/ 0.9 GALLON	4
KS Storm Patch Premium Wet/Dry Patching Cement Black	KS0083600	01 Cart	10 fl oz cartridge	12
KS Storm Patch Premium Wet/Dry Patch & Seal Clear	KS0083650	01 Cart	10 fl oz cartridge	12
KS Storm Patch Acrylic Patch & Seal White	KS0085100	01 Cart	10 fl oz cartridge	12
KS Storm Patch Acrylic Patching Cement White	KS0085100	16 GAL	115 OZ/ 0.9 GALLON	4

PATCH & REPAIR FABRICS AND TAPES				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Storm Patch Flexx Sealer 2”X10’	KS0018110	99 ROLL	2” x 10’	16
KS Storm Patch Flexx Sealer 2”X3’	KS0018103	99 ROLL	2” x 3’	12
KS Storm Patch Black Patching Tape	KS0018225	99 ROLL	2” x 42”	12
KS Storm Patch White Patching Tape	KS0018200	99 ROLL	2” x 42”	12
KST Storm Patch 4” Polyester Fabric	KS0018304	99 ROLL	4” x 50’	12

PATCH & REPAIR AEROSOLS				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Storm Patch Aerosol White	KS0065100	18 Aero	12 oz	6
KS Storm Patch Aerosol Black	KS0065125	18 Aero	12 oz	6
KS Storm Patch Aerosol Clear	KS0065150	18 Aero	12 oz	6
KS Storm Patch Aerosol Galvanizing Primer	KS0065200	18 Aero	12 oz	6

PRIMERS				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Storm Patch Acrylic Rust Primer	KS0034800	16 GAL	115 OZ / 0.9 GALLON	4
KS Storm Patch Acrylic Rust Primer	KS0034800	20 PAIL	4.75 Gallon Pail	1
KS Acrylic Concrete Primer	KS0034900	20 PAIL	4.75 Gallon Pail	1

DRIVEWAY COATINGS				
SKU DESCRIPTION	PRODUCT NUMBER	SIZE CODE	SIZE DESCRIPTION	QTY/CASE
KS Emulsion Driveway Sealer (3YR)	KS0073300	20 Pail	4.75 Gallon Pail	1
KS Emulsion Driveway Sealer (3YR)	KS0073300	27 Drum	55 Gallon Drum	1
KS Emulsion Driveway Sealer & Filler (5YR)	KS0073600	20 Pail	4.75 Gallon Pail	1
KS Emulsion Driveway Sealer & Filler (5YR)	KS0073600	27 Drum	55 Gallon Drum	1
KS Premium Emulsion Driveway Sealer & Filler (7YR)	KS0073900	20 Pail	4.75 Gallon Pail	1
KS Premium Emulsion Driveway Sealer & Filler (7YR)	KS0073900	27 Drum	55 Gallon Drum	1
KS Pourable Driveway Crack Filler	KS0075100	16 Gal	115 oz/ 0.9 Gallon	4
KS Trowel Grade Crack Filler	KS0075200	16 Gal	115 oz/ 0.9 Gallon	4



