

KOOLSEAL

REFLECTIVE ROOF COATINGS



STORM PATCH® WET/DRY PATCH AND SEAL KS0083350 CLEAR

FEATURES & BENEFITS

- Satisfaction Guaranteed
- Patch & seals vents, gutters, skylights, chimneys and a variety of roof materials
- Elastic sealant with excellent adhesion
- Protects against the elements, extending the life of the roof



PRODUCT DESCRIPTION

Kool Seal® Storm Patch® Wet/Dry Patch & Seal (KS0083350) is a clear, elastic sealant with excellent adhesion that patch and seals vents, gutters, skylights, chimneys and a variety of roof materials.

RECOMMENDED USES

- Metal, aluminum, PVC, fiberglass/asphalt shingles, cedar shake, acrylic roof coatings, cement and slate
- Not recommended for use on polystyrene insulation or rubber roof

ORDERING INFORMATION

| Part Number | Color/Size |
|--------------|-----------------------------|
| KS0083350-01 | Clear (10 fl oz Cartridge) |

PRODUCT CHARACTERISTICS

| | |
|---------------|--|
| Technology | Tripolymer |
| Color | Clear |
| Volume Solids | 61% ± 2% |
| Weight Solids | 63% ± 2% |
| VOC | 341 g/L |
| Drying Time | Allow 24 hours between coats. Cures in 1-3 days. |

Dry time is temperature, humidity and film thickness dependent

COVERAGE RATES

Linear coverage: 1/8" Bead Application-96.7 linear ft
1/4" Bead Application-24.2 linear ft

KOOLSEAL

REFLECTIVE ROOF COATINGS



STORM PATCH® WET/DRY PATCH & SEAL KS0083350 CLEAR

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Surface must be power washed (minimum 2,000 psi) to remove dirt, and other foreign matter which could prevent proper adhesion. Surfaces must be completely dry prior to coating. **IMPORTANT: Where ponding water conditions persist beyond 48 hours, roof drains or other corrective measures must be installed to eliminate water build-up prior to coating the roof.** Tighten or replace loose screws. Apply Kool Seal® Storm Patch® Acrylic Rust Primer to existing rusted areas.

APPLICATION

Can be applied in wet or dry conditions and in temperatures ranging from 25°F to 100°F. Do not use in areas of continuous submersion (i.e. aquariums or swimming pools). Do not use in areas where temperatures exceed 200°. Do not apply to frosty or icy surfaces. Can be coated with Kool Seal Elastomeric Coating in 24 hours.

Apply with trowel or putty knife, tooling into seams and cracks. Apply at a rate of 1/8" per coat, not exceeding 1/4" or more, reinforce patch with Kool Seal® Storm Patch® Patching Fabric. For specific application guidelines, call 888-321-KOOL (5665).

CLEANUP

Mineral spirits. Follow manufacturer's instructions for safe use.

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED WARRANTY

From date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

TECHNICAL SERVICES

1-888-321-KOOL (5665) www.koolseal.com

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.