



## KOOL SEAL® PREMIUM ROOF PAINT

### FEATURES & BENEFITS

- 5 Year warranty
- 100% Acrylic formula
- Tintable to a wide range of colors
- Available in flat, satin and semi-gloss finish
- Available sizes: 5-gallon

### PRODUCT DESCRIPTION

Kool Seal® Premium Roof Paint is a 100% acrylic coating that is tintable to a wide range of colors. This premium formulation is UV resistant, and won't chalk, crack or peel from a properly prepared surface. This decorative coating resists fading and the dry coating of this paint mildew resistant.

### RECOMMENDED USES

- Concrete Roof Tiles
- Metal Roofs

### ORDERING INFORMATION

Part Number	Sheen/Size
KST053500-20	Extra White Flat (5-Gallon Pail)
KST053505-20	Deep Base (5-Gallon Pail)
KST053509-20	Ultra Deep Base Flat (5-Gallon Pail)
KST053510-20	Extra White Satin (5-Gallon Pail)
KST053515-20	Deep Base Satin (5-Gallon Pail)
KST053519-20	Ultra Deep Base Satin (5-Gallon Pail)
KST053520-20	Extra White Semi Gloss (5-Gallon Pail)
KST053525-20	Deep Base Semi Gloss (5-Gallon Pail)
KST053529-20	Ultra Deep Base Semi Gloss (5-Gallon Pail)



### PRODUCT CHARACTERISTICS

Technology	Acrylic
Tint Bases	Extra White / Deep / Ultra Deep
Volume Solids	36% ±2%
Weight Solids	50% ±2%
VOC	<50 g/L
Drying Time	<b>@ 77°F, 50% RH</b> To touch: 2 hours To recoat: 4 hours Temperature and humidity dependent

*Dry time is temperature, humidity and film thickness dependent*

### APPLICATION RATE FOR EACH COAT

Flat Cement Tile: 200 sq. ft/gal  
Barrel Cement Tile: 150 sq.ft/gal  
Metal: 200 sq.ft./gal

Note: Actual coverage will vary depending on porosity of surface. Apply two coats to all surfaces at the above rates.

### *SURFACE PREPARATION*

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**Uncoated:** Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, peeling and defective coatings, chalk, form release agents, moisture curing membranes, etc. Mildew – Remove before painting by washing with a solution of 1 quart liquid bleach and 3 quarts of water. Apply the solution and scrub the area. Allow the solution to remain on the surface for 10 minutes. Rinse with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution. Sand glossy surfaces dull. Concrete and mortar must be cured - usually about 30 days. If coating before 30 day cure, or if pH is higher than 8, prime with a concrete primer.

**Previously Painted:**

All old, peeling, flaking paint must be removed.

### *APPLICATION*

For most applications, a minimum of two coats is required for maximum performance and uniform appearance. Stir thoroughly before and during application. Intermix all containers to ensure color uniformity.

**DO NOT THIN.**

Brush – Use a nylon/polyester brush

Roller – Use a 3/8" - 1/2" nap cover

Spray – Airless Pressure: 2000 psi Tip: .015" - .025"

### *CAUTIONS*

For exterior use only. Protect building inlets from product vapors or fumes. **DO NOT** allow product to freeze. Protective clothing, gloves and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. **DO NOT** allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle.. Seal container when not in use. Do not walk on coating until fully cured.

### *APPLICATION CONDITIONS*

Do not apply below 50°F or when rain is forecast. Application during periods of low temperature or high humidity will extend dry time. Allow 4-6 hours for coating to dry prior to being subjected to rain, heavy dew or temperatures below 50°  
**KEEP FROM FREEZING.**

### *CLEANUP*

Clean hands, tools, and spills and spatters immediately with soap and warm water. After cleaning, flush spray equipment to prevent rusting of the equipment.

### *5 YEAR LIMITED WARRANTY*

For 5 years from the date of purchase, if this product fails to perform in accordance with the specifications set forth on the label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferrable. This warranty excludes failure due to improper surface preparation, structural defects or failure of other previously applied products. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

### *TECHNICAL SERVICES*

**1-888-321-KOOL (5665)    [www.koolseal.com](http://www.koolseal.com)**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.